

Public Abstract

First Name:Christopher

Middle Name:Anthony

Last Name:Yeckel

Adviser's First Name:Randy

Adviser's Last Name:Curry

Co-Adviser's First Name:

Co-Adviser's Last Name:

Graduation Term:SS 2010

Department:Electrical Engineering

Degree:MS

Title:SPECTROGRAPHIC TEMPERATURE MEASUREMENT OF A BREAKDOWN ARC WITHIN THE RIMFIRE GAS SWITCH

A procedure for obtaining the temperature of optically thick plasma is described. The plasma is in the form of a gas breakdown arc which conducts approximately 10-kJ of energy in $1\text{-}\hat{1}\frac{1}{4}\text{s}$. A spectrographic analysis of the trigger-section of the 6-MV RIMFIRE laser triggered gas switch used in Sandia National Laboratory's "Z-Machine" has been completed. It is assumed that the breakdown plasma has achieved approximate local thermodynamic equilibrium allowing a black-body temperature model to be applied. This model allows the plasma temperature and radiated power to be approximated. The gas dielectric used in these tests was pressurized SF₆. The electrode and the insulator materials are stainless steel and PMMA, respectively. A spectrum range from 250 to 450 nanometers has been observed and calibrated using two spectral irradiance lamps and three spectrograph gratings. The approximate plasma temperature and radiated power are reported.